

euFRAME CONCEALED PANEL

version FBWP-02 and

FBWP-PXS-02 with proximity sensor



euFRAME Data Sheet

The euFRAME (FBWP-02) concealed panel is built into a wall concealed panel serving as a fixed 'dock' for iPad® (2017), iPad® Air, iPad® Air 2 or iPad® Pro 9.7" tablet manufactured by Apple, and dedicated, among others, to display information or control automatic systems of a smart building. The panel consists of a concealed box with a built-in intelligent power supply unit and a microprocessor controller, and also of a decorative external frame, masking the interface between the box and a wall, and keeping the tablet in the appropriate position. The frame is attached to the box with the use of strong magnets. Frames are made of high-quality mineral composites, and come in many colors and designs. The FBWP-PXS-02 version of the concealed panel features a proximity sensor. After detecting that a person intends to use a tablet, the sensor switches it out of the sleep mode. The panel can be fitted in a vertical or a horizontal position. The iPad® is not included with euFRAME, and needs to be purchased separately.

Applications:

- Use applications installed on your iPad® (2017), iPad® Air, Air 2 or iPad® Pro 9.7" to control different functions and devices of your intelligent home or office.
- Complete control of all audio, video, lighting and other devices of conference and training rooms.
- Interactively & dynamically present meeting agendas, training programs, and other information in front of conference and training rooms.

Technical Specification:

Supply voltage:	110 – 240 V AC, 50–60Hz
Power consumption:	max. 14 W
Input current consumption:	0.35 A/115 V, 0.2 A/230 V
Inrush current:	30 A/115 V, 50 A/230 V
Box dimensions:	299.7 x 182.9 x 49.1 mm
Frame dimensions:	315.4 x 192.4 x 4/6 mm
Type of walls:	solid brick walls (made of concrete, bricks, etc.) and cavity walls (made of drywall or wood).
Protections:	Overheating and overload protection (triggered when load current exceeds 2.5 A).
Alarm sound:	89 dB at 10 cm
Operating temperature:	0°C to +50°C
Relative humidity:	≤90%, no condensation.
Degree of protection:	IP20
Alarm output current:	max. 120 mA, R _{ON} < 2.2 kΩ
Detection of approach:	Step adjustment: <i>Normal</i> 60 cm, <i>High</i> 1 m

Address:

Eutonomy Sp. z o.o. Sp. K.
ul. Piotrkowska 121/3a
90-430 Łódź, Poland

Contact:

www.eutonomy.com/contact
email: sales@eutonomy.com
Tel: +48 42 942 0730

The copyright to the content of this brochure is reserved exclusively for Eutonomy Sp. z o.o. Sp. K. This content must not be copied or republished without the permission of the copyright owner.



Content of the boxes:

1. Concealed wall panel box.
2. Instruction manual.
3. Protective plate.
4. Frame removal tool.
5. Selected decorative frame (ordered, sold and packaged separately).

Where to order:

- Eutonmy: e-shop.eutonmy.com
- Fibaro: showrooms & sales network.
- Worldwide: www.eutonmy.com/where-to-buy/



The *ESSENTIAL* Collection...

... includes five colour designs (see the picture above): **Bleached Black***, **Stone**, **Ivory**, **Desert Sand** and **White**). These are natural colors of the highest quality mineral composites we use to manufacture the frames.

*Please note that specifically Bleached Black is not a "uniform" color - it can show lighter discolorations (especially along the angled planes) natural to this porous material - somewhat resembling aged or oxidated material. Such discolorations are not subject to complaints and will not be treated as faulty goods.

The *INDIVIDUAL* Collection...

... Allows achieving a unique fit between your interiors and the decorative frame of the euFRAME. Frames can be painted in any of the RAL or NCS colors either imatt or semi-gloss. Please be aware that it can take up to 3 weeks to dispatch an individually painted decorative frame..